

**Professional**

Advanced Wireless Network Camera

DN-16063-1
4016032295693

Suits your surveillance needs at day and night

Feeling safe is priceless. For this reason you should never compromise on security. Do we not have enough worries these days? Hand a part over: This camera is ideal for reliable indoor monitoring. The robust design raises no doubts that this might be a toy. The H.264 video standard ensures smooth, crystal clear images at a lower network load compared to legacy technologies. Thanks to infrared lighting the high resolution offers details even at night. Equipped with 2-way audio system the camera can also be deployed for hand-free intercom operation. Not only the hardware is convincing: With auto motion detection and supplied software your equipment is future-proof and you save a lot of time! Just focus on the essential instead of painstakingly going through the daily recordings! Video images are only generated in case of activity.

- True Day and Night surveillance
- Wireless LAN according to the newest 11n standard for fluent image transmission
- Meets the highest security requirements (WPA2 Encryption)
- Large aperture lens (F1.9)
- Prime lens: f4.6mm
- Viewing Angle: 60°
- High resolution and best video performance
- Enhanced motion detection and alarm notification functions
- Alarm and event notification by FTP and Email
- Powerful mobile surveillance supporting iPhone, Blackberry and WinCE devices
- Low-latency video streaming with H.264 compression format
- Hybrid digital / analog video output
- Built-in microphone & external microphone input
- External audio output
- External alarm input
- LAN Speed: 10/100Base-TX Ethernet
- Supported Protocols: DDNS, PPPoE, DHCP, NTP, SNTP, TCP/IP, ICMP, SMTP, FTP, HTTP, RTP, RTSP
- Frame Rate NTSC: 30, PAL: 25
- Number of Online Users: 10
- Security: Multiple user access levels with password protection
- Management by web browser or CMS software for up to 16 network cameras control simultaneously
- Compatible to the future proof ONVIF Standard
- Image Sensor: 1/3" HR color CCD sensor
- Resolution: 768x494 pixel NTSC / 752x582 pixel PAL
- Min Illumination 0 Lux (IR ON)
- Shutter Speed 1/60 (1/50) to 1/100,000 sec.
- IR effective distance up to 10 meters
- Operating temperature: 0°C - 40°C
- Power source (±10%): DC12V / 1A
- Dimensions (mm): 152.5(L) x 115.2(W) x 40.2(H)
- Operating system independent, supports e.g. Windows, Linux, Mac-OS and Sun

PACKAGE CONTENT

- IP-Camera
- Wireless LAN Adapter
- Power Adapter
- Manual
- Software CD
- Mounting accessories
- RJ45 Cable



